



1806 Asbury Road
 Erie, PA 16505-3025
 Phone: (814) 833-9814
 Fax: (814) 833-9817

Valve Numbering Format

Click here to visit the Flexi-Hinge website at www.flexi-hinge.com

Pipe Size	Series	Description			
1	- 502M	- Male Threaded Ends			
1.25	- 503	- 150# Flanged Raised Face			
1.5	- 504	- 150# Flanged Flat Face			
2	- 513	- Victaulic Grooved			
2.5	- 514	- Plain Ends			
3	- 517	- 150# Flanged Ends Expansion			
4	- 517M	- Male Threaded Ends Expansion			
5	- 518	- 125# Cast Iron Flexi-Hinge® Wafer			
6	- 581	- 150# Long Pattern Flanged Ends			
8	- 588	- Steel or Stainless Steel Wafer			
10	- 595	- 150# Flanged Ends Foot Valve			
12	- 595M	- Male Threaded Ends Foot Valve			
14	-				
16	-				
18	-				
20	- Examples :				
22	-				
24	-				
	12"- 518-4310	12" Cast Iron Flexi-Hinge® Wafer with Aluminum Internals and Buna-N Seal			
	3"-502M-1231	3" Steel MTE Body with Stainless Steel Internals, Silicone Seal, and Stainless Steel Spring			
	6"-503-2240	6" 316 Stainless Steel 150# Flanged Ends with 316 Stainless Steel Internals, and Viton Seal			
	10"595-1211	10" Foot Valve with 150# Flanged Ends, Stainless Steel Internals, Buna-N Seal, Stainless Steel Spring, and 316 Stainless Steel Screen			

INTERNSIONS				Description
BODY	INTERNAL	SEALS	SPRING	
1	X	X	X	Carbon Steel Body
2	X	X	X	Stainless Steel Body
3	X	X	X	Aluminum Body
4	X	X	X	Cast Iron Body
5	X	X	X	Cast Steel Body
6	X	X	X	Cast Stainless Steel Body
7	X	X	X	Cast Aluminum Body
8	X	X	X	Cast Ductile Iron
9	X	X	X	Epoxy Coated Body
2	X	X		Stainless Steel Internals
3	X	X		Aluminum Internals
8	X	X		PVC Plastic Internals
1	X			Buna-N Seal
2	X			EPDM Seal
3	X			Silicone Seal
4	X			Viton Seal
0				No Spring
1				Stainless Steel Spring
2				Special Operation